## SYNTHETIC/RUBBERISED BASKETBALL COURT WITH ALLIED ACCESSIRIES

andele description de la company de la compa								والمعاددة المارية	Ser
	(g) Seal Coat with stone dust H. An open saucer drains at a lower end 1.6" Retaining or Edge wall for support.	(f) Lay a 20 mm compacted thick hot mix A.C course.	(e) Lay a 30 mm compacted thick hot mix Asphalt BM course.	(d) Lay a layer of 85mm/65mm compacted water bound macadam in one/two layers respectively. WBM to be densely compacted by keying and inter locking the stones to ensure that no settlement takes places.	(c) Carry out anti-termite and weedicide on the total area by spraying.	(b) Compaction of the sub base will be by 8-10 ton roller.	(a) Dressing of soil after removing existing grass and weeds.	Outdoor Asphalt Base	Specification
								6000	VID
			•						Remarks

Ser	2	e proportion de la recomme de la colonidad	A PARTY OF THE PAR		en de servicio de la composición de la		44 g			and the same of th					
Specification	Polypropylene Modular Tiles	(a) Tile Dimension : 1 feet x 1 feet.	(b) Tile Thickness : 15.7mm.	(c) Tiles Weight : 330 Gms.	(d) Weight Taking Capacity: 26 Tons.	(e) Material : Polypropylene (PP).	(f) Tile Fixations : 7 Points (Female/Male in each side).	(g) Side remission: 0,0-1,2 mm.	(j) Painting receptivity : Very Good.	(k) HSN Code 3918.	(I) Solvent Resistance : Excellent.	(m) Fire Resistance : M4.	(n) Mate surface with anti- slippery finishing.	(o) Warranty: 5 Years on breakage/falting.	
Qty	6000		1								24				
Remarks															

	6		- 5											
Pro	D	000						4		<	······································		ب	No
Providing & fixing required drain system along the court.	<u>Drain System.</u>	(a) Fabricate all around fence 10' in heightened covering with one opening in the form of gate 3' wide and 8 high at the entrance of the Court.	Chain Link fence.	(d) Dunking Rim with spring mechanism.	(c) Frame coated die made frame with built in brackets for mounting.	(b) 25 mm back fiber glass board with International Standard die made and ring.	(a) Poles: 8" round pipe with 3.2 mtr distance from the board.	Basketball Pole and Accessories.	(d) Full wiring from out control panel to poles and fixere complete.	(c) Four Poles with MCBs.	(b) One double door weather proof distribution board with MS sheet.	(a) 100 w, 4 Led flood light fixtures on the four poles.	Flood Lighting LED.	+
	1 JOB		LS					_					4	Qty
														<u>Remarks</u>